



Supplier Compliance Quick Receive (B-12) Label (2" x 4") Specification Sheet

For additional detail, refer to the *AIAG B-10 Guidelines – June 2004*

Supplier
Block Title = (13V) Supplier
Symbology = Code 39
Data = H-D assigned supplier ID number.
Data Identifier (DI) = 13V
Maximum Length = 9: Max Data Chars = 6
 DI Chars = 3



Code 39 Specifications

- Industry Standard is the Automotive Industry Action Group (AIAG)
- “X” Dimension shall be in the range of 0.33 MM (0.013 inch) to 0.43 MM (0.017 inch)
- Bar code height shall be a minimum of 13 MM (0.5 inch)
- Quiet zone (blanks space at each end of bar code) shall be a minimum of 6.3 MM (0.25 inch).
- Bar code shall meet a minimum ANSI print quality grade of “C”
- Human readable data must be 0.25 inches or 20 points or 3 LPB
- Row/Block height must be 1 inch tall.

ASN Shipment ID / Quick Receive ID
Block Title = (2S) ASN Shipment ID / Quick Receive
Symbology = Code 39
Data = Supplier assigned ASN/Shipment ID number.
Data Identifier (DI) = 2S
Maximum Length = 10: Max Data Chars = 8
 DI Chars = 2

<u>Customer Name:</u> Harley-Davidson Motor Company	<u>Label Purpose/Use:</u> QUICK RECEIVE: Customer segment of a B-12 label to be used on the shipment’s packing slip.	<u>NOTE:</u> Actual size is 2” x 4”. Any dimensions that are not otherwise specified on this page SHALL be in compliance with the AIAG B-10 Guidelines, June 2004 (www.aiag.org).	
<u>Harley-Davidson Contacts:</u> Cassandra Olson, Electronic Commerce Lead – (414) 423-2222 Kelly Barbara, Corporate EDI Coordinator – (717) 852-6526	<u>Issue Date:</u> March 1999	<u>Version . Release:</u> 4010.00	<u>Specification ID Number:</u> B-12 (Quick Receive) Label