



Supplier Compliance Quick Receive (B-12) Label (2" x 4") Specification Sheet

For additional detail, refer to the *AIAG B-10 Guidelines – June 2004*

Supplier

Block Title = (13V) Supplier

Symbology = Code 39

Data = H-D assigned supplier ID number.

Data Identifier (DI) = 13V

Maximum Length = 9: Max Data Chars = 6
DI Chars = 3

(13V) Supplier

K0251



(2S) ASN Shipment ID
/Quick Receive ID

87651387



Code 39 Specifications

- Industry Standard is the Automotive Industry Action Group (AIAG)
- "X" Dimension shall be in the range of 0.33 MM (0.013 inch) to 0.43 MM (0.017 inch)
- Bar code height shall be a minimum of 13 MM (0.5 inch)
- Quiet zone (blanks space at each end of bar code) shall be a minimum of 6.3 MM (0.25 inch).
- Bar code shall meet a minimum ANSI print quality grade of "C"
- Human readable data must be 0.25 inches or 20 points or 3 LPB
- Row/Block height must be 1 inch tall.

ASN Shipment ID / Quick Receive ID

Block Title = (2S) ASN Shipment ID /
Quick Receive

Symbology = Code 39

Data = Supplier assigned ASN/Shipment ID
number.

Data Identifier (DI) = 2S

Maximum Length = 10: Max Data Chars = 8
DI Chars = 2

<u>Customer Name:</u> Harley-Davidson Motor Company		<u>Label Purpose/Use:</u> QUICK RECEIVE: Customer segment of a B-12 label to be used on the shipment's packing slip.		NOTE: Actual size is 2" x 4". Any dimensions that are not otherwise specified on this page SHALL be in compliance with the AIAG B-10 Guidelines, June 2004 (www.aiag.org).	
<u>Harley-Davidson Contacts:</u> Jaison Battle, Director of EDI – (414) 343-7584 Kelly Barbara, Corporate EDI Coordinator – (717) 852-6526		<u>Issue Date:</u> March 1999		<u>Version . Release:</u> 4010.00	
				<u>Specification ID Number:</u> B-12 (Quick Receive) Label	



MRO Supplier Compliance Quick Receive (B-12) Label (2" x 4") Specification Sheet

For additional detail, refer to the *AIAG B-10 Guidelines – June 2004*

Supplier

Block Title = Packing List #

Symbology = Code 39

Data = H-D assigned supplier ID number.

Maximum Length = 8: Max Data Chars = 8

Purchase Order #

TS987560



Packing List #

03262009



Code 39 Specifications

- Industry Standard is the Automotive Industry Action Group (AIAG)
- “X” Dimension shall be in the range of 0.33 MM (0.013 inch) to 0.43 MM (0.017 inch)
- Bar code height shall be a minimum of 13 MM (0.5 inch)
- Quiet zone (blanks space at each end of bar code) shall be a minimum of 6.3 MM (0.25 inch).
- Bar code shall meet a minimum ANSI print quality grade of “C”
- Human readable data must be 0.25 inches or 20 points or 3 LPB
- Row/Block height must be 1 inch tall.

ASN Shipment ID / Quick Receive ID

Block Title = Purchase Order #

Symbology = Code 39

Data = Supplier assigned ASN/Shipment ID number.

Maximum Length = 10: Max Data Chars = 10

Customer Name:

Harley-Davidson Motor Company

Label Purpose/Use: QUICK RECEIVE: Customer segment of a B-12 label to be used on the shipment's packing slip.

NOTE: Actual size is 2" x 4". Any dimensions that are not otherwise specified on this page SHALL be in compliance with the AIAG B-10 Guidelines, June 2004 (www.aiag.org).

Harley-Davidson Contacts:

Jaison Battle, Director of EDI – (414) 343-7584

Kelly Barbara, Corporate EDI Coordinator – (717) 852-6526

Issue Date:

March 2009

Version . Release:

4010.00

Specification ID Number:

B-12 (Quick Receive) Label